

# Safety Data Sheet

LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

Page 1 of 7

SDS No.: 422581 V001.2

Date of issue: 17.01.2020

# Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML

Intended use: Cy anoacry late

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

+61 (3) 9724 6444 Phone:

**Emergency information:** 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

# Section 2. Hazards identification

#### Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

# **GHS Classification:**

**Hazard Class Hazard Category** Target organ

Flammable liquids Category 4 Skin irritation Category 2 Category 2A Serious eye irritation Category 3

Target Organ Systemic Toxicant respiratory tract irritation

Single exposure

Hazard pictogram:



Signal word: Warning

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

**Hazard statement(s):** H227 Combustible liquid. H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Precautionary Statement(s):** 

**Prevention:** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapors, mist, or spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

P370+P378 In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

**Storage:** P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

#### **Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

## Section 3. Composition / information on ingredients

**General chemical description:** Mixture

**Identity of ingredients:** 

Chemical ingredients	CAS-No.	Proportion
Ethyl 2-cyanoacrylate	7085-85-0	60- <= 100 %
non hazardous ingredients~		30- <= 60 %

## Section 4. First aid measures

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

**Ingestion:** Ensure that breathing passages are not obstructed. The product will polymerise

immediately in the mouth making it almost impossible to swallow. Saliva will slowly

separate the solidified product from the mouth (several hours).

Skin: Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a

spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate

enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage

maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eyes: If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help

to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of

cy anoacry late trapped behind the eyelid cause any abrasive damage.

**Inhalation:** Move to fresh air, consult doctor if complaint persists.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

## Section 5. Fire fighting measures

**Suitable extinguishing media:** Foam, extinguishing powder, carbon dioxide.

Fine water spray

Improper extinguishing media: High pressure waterjet

Combustion behaviour: Combustible Liquid

Keep away from heat, spark, and open flames.

Decomposition products in case of

fire:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of nitrogen.

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

#### Section 6. Accidental release measures

Personal precautions: Ensure adequate ventilation.

Avoid skin and eye contact. Wear protective equipment.

**Environmental precautions:** Do not let product enter drains.

Clean-up methods: Do not use cloths for mopping up. Flood with water to complete polymerization and

scrape off the floor. Cured material can be disposed of as non-hazardous waste.

Dispose of contaminated material as waste according to Section 13.

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

## Section 7. Handling and storage

**Precautions for safe handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash

thoroughly after handling.

Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal

burns.

**Conditions for safe storage:** Store in a cool place in closed original container.

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C

(35.6 - 46.4 °F)

# Section 8. Exposure controls / personal protection

National exposure standards:

None

**Engineering controls:** Ensure good ventilation/extraction.

**Eye protection:** Wear protective glasses.

**Skin protection:** Protective clothing that covers arms and legs.

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

**Respiratory protection:** If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

#### Section 9. Physical and chemical properties

**Appearance:** colourless to yellowish

liquid

Odor: irritating
Odor threshold (CA): 1 - 2 ppm
Specific gravity: 1.1

**Boiling point:** > 149 °C (> 300.2 °F) **Flash point:** 80 - 93 °C (176 - 199.4 °F)

(Tagliabue closed cup)

Vapor pressure: < 0.5 mm hg

Vapor density: 3

**Auto ignition:** 485 °C

**Decomposition temperature:** 

## Section 10. Stability and reactivity

**Stability:** Stable under recommended storage conditions.

**Conditions to avoid:** Keep away from sources of ignition and naked flames.

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

**Incompatible materials:** Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and

alcohols.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of nitrogen.

# Section 11. Toxicological information

**Health Effects:** 

**Ingestion:** Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It

is almost impossible to swallow.

Skin: Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacry lates generate heat on solidification. In rare circumstances a large drop will burn the

skin. Cured adhesive does not present a health hazard even if bonded to the skin.

**Eyes:** Irritating to eyes. Causes excessive tearing. Eyelids may bond.

**Inhalation:** Exposure to vapors above the established exposure limit results in respiratory irritation, which

may lead to difficulty in breathing and tightness in the chest.

#### Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Ethyl 2-cyanoacrylate	LD50	> 5,000 mg/kg	oral		rat	OECD Guideline 401 (Acute
7085-85-0	LD50	> 2,000  mg/kg			rabbit	Oral Toxicity)
			dermal			OECD Guideline 402 (Acute
						Dermal Toxicity)

# Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Ethyl 2-cyanoacrylate	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute
7085-85-0				Dermal Irritation / Corrosion)

#### Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate	irritating	72 h	rabbit	OECD Guideline 405 (Acute
7085-85-0				Eye Irritation / Corrosion)

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	not specified

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

## Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

# Section 12. Ecological information

**General ecological information:** Do not empty into drains / surface water / ground water.

#### Persistence and degradability:

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
Ethyl 2-cyanoacrylate	not readily biodegradable.	aerobic	57 %	OECD Guideline 301 D (Ready
7085-85-0				Biodegradability: Closed Bottle
				Test)

#### Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Ethyl 2-cyanoacrylate	0.776				22 ℃	EU Method A.8 (Partition
7085-85-0						Coefficient)

# Section 13. Disposal considerations

Waste disposal of product: Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised

landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

# Section 14. Transport information

# Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

## Marine transport IMDG:

Not dangerous goods

# LOCTITE 406 WICKING GRADE INSTANT ADHESIVE known as Loctite 406 500ML AU

#### Air transport IATA:

UN no.: 3334

Proper shipping name: Aviation regulated liquid, n.o.s. (Cy anoacrylate ester)

Class or division: 9
Packing group: III
Packing instructions (passenger) 964
Packing instructions (cargo) 964

Additional Information IATA: Primary packs containing less than 500ml are unregulated by this

mode of transport and may be shipped unrestricted.

# Section 15. Regulatory information

SUSMP Poisons Schedule None

## Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Medicines of Drugs and Poisons

**Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1,2

**Date of previous issue:** 24.02.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for

additional assistance.